Oblod

GOOGLE IS A TRADEMARK OF GOOGLE LLC







Apple MFi Manufacturer

Catalogue

For Your Intelligent Life



















CviCloud Corporation 瀚雲科技股份有限公司

CviCloud (SZ) Limited 瀚云信息技术(深圳)有限公司

CviCloud Limited 瀚雲科技有限公司

CviLux Group

About Us

Founded in 1990. CviLux dedicates in manufacturing & selling connectors, FFC, and Wire harnesses. Our products are mainly for the application of consumer electronic. computers, communication and electrooptical. CviLux headquarters with highprecision automatic production line is located in Tamshui, Taipei and operates totally 8 plants at Tamshui in Taiwan, Dongguan, Suzhou, Chong Qing, Anhui area in China and Laos to meet worldwide delivery trend.

CviLux products have been distributed through European, Asian and American markets. With integrated sales network. CviLux is able to connect its Asian production bases and sales partners all over the world in a very short time. With the efficient information system & global organization ability, CviLux provides good local service worldwide

CviLux will keep extending overseas sales network and co-operating with world- famous enterprises on OBM/ODM/OEM cases. Besides, we will also be allied with technical partners to enlarge the capacity and accelerate improving R&D and manufacturing techniques, which can create much more add-on value products to satisfy our customers and markets. We are marching to be a main supplier on global electronic materials supply chain.

In the past, CviLux stood for stable, speedy, and quality. In the future, CviLux will go on to offer faster, better and add-on value products with great service to win your trust.

Strenath

- Apple MFi manufacturer (C.M. 6.6) and HomeKit Provider
- Global Sales Marketing Company in IT Industry over 29 Years
- Local Warehouse & Logistics Available in USA, Europe and Asia.
- Integrated Production & Marketing Strategy.
- R&D Team Creating Innovation & More Add-On Value Products

FOR YOUR INTELLIGENT LIFE

Opro9 is originated from CviLux Group. CEO, Mr. Steve Yang, has good experience in the electronic connector industry over 40 years and create the brand "CviLux" into the well-known field of connectors in the world. "Connect" is not only a tool to bring our life together, but also an inheritance. Opro9 holds original faith of CviLux and looks into the future. In addition, we not only pay attention on ODM business but also keep doing IOT product research and development as well. Furthermore , we can help you find the solution to improve your living. In the future we will expand our product lines and launch more and more articles for your intelligent life.

Sales Rep. & O2O Distributor Required.

Service: service@opro9.com

(The product is covered with USD one million Product Liability Insurance.)

Apple MFi Manufacturer



























IATF 16949

ISO 9001

ISO 14001

QC080000

OHSAS18001

ISO14064

























reddot award 2017 honourable mention





















Opro9 has professional cloud services, in addition to HomeKit's original iCloud cloud service, Opro9 also provides a differentiated cloud service experience.



Opro9 is a global brand. We have passed ISO 9001, 14001, 14064, QC 080000, OHSAS18001, vide consumers with the highest quality products.



Opro9 has extensive experience in integration of software, hardware and cloud platform systems, and has the ability to integrate and develop crossplatform systems.



System Integration

Opro9 have a good supply chain partnership. Customized solution integration experience, HomeKit system integration solution service.



Opro9 has a customized R&D team to provide customized product development services and complete after-sales services.



Industrial Design

Opro9 has an experienced industrial design team. Received worldwide Design Award experience, The design team has a wealth of design strength.



Operating System

Opro9 as MFi manufacturer, product certification by HomeKit. Apple HomeKit system has the advantages of high security encryption.



Experience


Opro9 provides users with rich context experience, guide users to create a dedicated situation experience.





ect the Future Oprog





















Smart Home · Care Center · Smart Factory Online Shopping • R&A Service • Push Notify







3RD PARTY CLOUD

Google · Alexa Apple · Baidu



API

Tmall · Tencent

Voice Command





Software Design iOS · UI/UX · Android









INTERNET





















Communication Scheme (Wi-Fi, BLE, LoRa, ...)



Hardware Design Firmware Design · Electronic Design Industrial Design · Mechanical Design

CviCloud





Lights







Security



Outlets



Locks



Thermostats



Cameras



Windows



Doorbells



Humidifiers



Garage Doors





Bridges



Speakers





Air Conditioners



Opro9 Home App

Compatible devices required





Apple MFi Manufacturer

















Intelligent Scenes

Smart Home Security Management Smart Lightning Management Smart Home Energy Saving Party and Special Scene Outdoor B2B Solutions









Light up Your Home with Smart Technology!



Smart Home Security Management

Opro9 Smart Home Security Management system makes you control the situation of your family and house anytime. It will record any wonderful moment and even protect your love.







Door & Window Sensor



Smart Lightbulb Socket




Smart Power Outlet



Smart Light (Switch) Control Box



Smart Light (0-10V) Dimmer Switch Control Box



Smart Lightning Management

Opro9 Smart Lighting Management system perfected to produce true-to-life colors on command, the system doesn't only put the brightest, most beautiful palette at your fingertips



Smart Lightbulb Socket



Smart Power Outlet



Smart Light (Switch) Control Box



Smart Light (0-10V) Dimmer Switch Control Box



Motion Sensor



Opro9 Smart Home Energy Saving make it come true that you can control the home appliances anytime. To save sources technologically, to make life more conveniently, to be friendly for environment, and to save money more than you think!



Smart Air Purifier



Smart Lightbulb Socket



Smart Power Outlet



Smart Light (Switch) Control Box



Smart Light (0-10V) Dimmer Switch Control Box



Motion Sensor



Party and Special Scene

Opro9 Party and Special scene management system can help users to control the feeling of the scene, give users and participants the best and delightful experience



Smart Aroma Diffuser



Smart Air Purifier



Smart Lightbulb Socket



Smart Power Outlet



Smart Light (Switch) Control Box



Smart Light (0-10V) Dimmer Switch Control Box



Motion Sensor



Opro9 outdoor scene management system can help users control and connect every outdoor device more intelligently and easily.



Smart Power Outlet



Smart Light (Switch) Control Box



B2B Solutions

Opro9 B2B Solution can raise the efficiency of company operation and lower energy consumption to satisfy the modern demands with high stability.



Smart Aroma Diffuser



Smart Air Purifier



Door & Window Sensor



Smart Lightbulb Socket



Smart Power Outlet



Smart Light (Switch) Control Box



Smart Light (0-10V) Dimmer Switch Control Box



Motion Sensor



Smart Aroma Diffuser

Support Wi-Fi controlled by way of APP To select the Humidification time (1H/3H/8H) Automatically turn off as waterless

Manual operation to 5 kinds of Scenario Lights and Color Lights on the APP

Humidifier initial set up.

Automatically start the humidity detected function, when the air humidity is reached under the humidifier set up

Wi-Fi specification
Wireless security
Protection
Noise
Adapter Rated voltage
Input voltage
Maximum power
Product Dimensions
Weight
Certifications

2.4GHz IEEE 802.11 b/g/n
WPA Personal, WPA2 Personal
Low-water level protection / waterless protection
<36dB
100V-240V, 50/60Hz
DC 24V / 1.0A
19W
86.8*113.3*209mm
0.476 kg
NCC, SRRC, ROHS











FHH106 Smart Air Purifier

Support Wi-Fi controlled by way of APP
Automatically detect the air dust concentration
Automatically detect if any smoke
Automatically control motor speed
Automatically indicate the working time accumulated
Automatically turn off as waterless
Automatically generate negative ions function in the air
Manual Select various 4 kinds of Scenario Lights on the APP

Wi-Fi specification Wireless security Adapter voltage Input voltage Maximum power Noise Product Dimensions Weight Certifications

2.4GHz IEEE 802.11 b/g/n WPA Personal, WPA2 Personal 100-240VAC, 50/60Hz DC 12V / 1A 11.5W <55dB 270*138*212mm 1.5 kg CE, TELEC, PSE, NCC, BSMI, SRRC











Smart Lightbulb Socket (US)

Smart lightbulb socket (United States, Europe, Taiwan version) can work with Ok Google and Apple Homekit, Wi-Fi wireless controlled by APP or Siri voice command Remote Turning On/Off, Dimmer Control.

Input Type Output Type Power Consumption Max External Load Product Dimensions LED

Line Voltage Connection Push Button Certification LED Notification 100-125V (US) E26/E27 5W (Max) 60W (US)

65 * 65 * 81 mm

Power Switch (Solid green). Wi-Fi Status (blinking blue)

Identify (Blinking red)

Max. 125VAC

Wi-Fi, Compliance to IEEE802.11 b/g/n WPA/WPA2

Power Switch, Reset FCC / NCC / TELEC / VCCI R:Device Indentify (Flash)

G: Power, Outlet in Use

B: Wi-Fi (Quick flash for adding into network)











Smart Power Outlet

Apple Homekit certifitied smart power outlet (United States, Taiwan, and Japan version)

Wi-Fi wireless controlled by APP or Siri voice command Metering feature to monitor the power usage Remote Turning On/Off Control

Output Port
Outlet Type
Relay Load
Line Voltage
Measuring Accuracy
Connection
Push Button
LED Notification

Over Load Protection Product Dimensions Certification 1
USA or Taiwan
Max. 10A (1,500W)
Max. 250VAC min. 100VAC
±10%
WiFi, Compliance to IEEE802.11 b/g/n WPA/WPA2
Power S witch, Reset
R: Device Indentify (flash)
G: Power , Outlet in Use
B: Wi-Fi (Quick flash for adding into network)
Provided (OCP)
65 * 65 * 81 mm

CE/FCC/NCC/TELEC/VCCI









FHH112 Dual System Outlet

Compatible with Alexa and works with Ok Google, Apple Homekit Wi-Fi Wireless Controlled by APP Metering feature to monitor the power usage Over Current Protection

Output Port
Outlet Type
Relay Load
Line Voltage
Measuring Accuracy
Connection
Push Button
LED Notification

Over Load Protection Product Dimensions Certification USA or Taiwan

Max. 10A (1,500W)

Max. 250VAC min. 100VAC

±10%

WiFi, Compliance to IEEE802.11 b/g/n WPA/WPA2

Power S witch, Reset

R: Device Indentify (flash)

G: Power , Outlet in Use

B: Wi-Fi (Quick flash for adding into network)

Provided (OCP)

65 * 65 * 81 mm

CE/FCC/NCC/TELEC/VCCI







Apple HomeKit Smart Lightbulb Control Box

Smart Lightbulb Control Box for 110V/220V, Dimming unavailable

Wi-Fi specification
Wireless security
Input Voltage
Load Current
Product Dimensions
Temperature range
Humidity range (Non-condensation)
Certification

2.4GHz IEEE 802.11 b/g/n WPA Personal, WPA2 Personal 100-240VAC~, 50/60Hz Maximum 600W/6A Confidentia Overload protection: 700W (OWP) l 111mm*45mm*27mm Storage Temperature(0~40°C), Operating Temperature (-20~65°C) Storage Temperature(10~90%), Operating Temperature (5~95%) CE, FCC, ETL, Wi-Fi, NCC, SRRC







Smart Lightbulb Control Box


Smart Lightbulb Control Box for 110V/220V Wi-Fi wireless controlled by APP Support Siri, Alexa, Google voice command Remote Turning On/Off Lighting Control

Wi-Fi specification
Wireless security
Input Voltage
Load Current
Overload protection
Product Dimensions
Temperature range
Humidity range (Non-condensation)
Certification

2.4GHz IEEE 802.11 b/g/n
WPA Personal, WPA2 Personal
100-240VAC~, 50/60Hz
Maximum 1500W / 15A
1750W (OWP) Confidentia
111mm*45mm*27mm
Storage Temperature(0~40°C), Operating Temperature (-20~65°C)
Storage Temperature(10~90%), Operating Temperature (5~95%)
CE, FCC, ETL, Wi-Fi, NCC, SRRC









Opro9 Motion Sensor

Opro9 Motion Sensor is an Homekit enable motion sensor and paired by Bluetooth, it can send notification of the motion trigger. Battery-powered and completely wireless and the sensor's location can be charged at any time for extreme convenience.

Product Dimensions Bluetooth specification Connection distance Input Voltage Detection distance Certification Temp range

Color

66mm*32mm*33mm
Bluetooth 5 and 2.4 GHz proprietary System-on-Chip
6 Meter
CR123A battery (3V) *1
≤ 8m
CE, FCC, ETL, NCC, SRRC
Storage Temperature(-20~80°C)
Operating Temperature (0~40°C)
Black, White









Opro9 Door & Window Sensor

Opro9 Door & Window Sensor is an Homekit enable sensor and paired by Bluetooth. The sensors can promptly notify you by your smart phone if someone attempts to access your home through a door and window. You can be sure that you and your family are protected.

Product Dimensions Bluetooth specification Connection distance Input Voltage Certification Temp range

Color

66mm*32mm*25mm
Bluetooth 5 and 2.4 GHz proprietary System-on-Chip
6 Meter
CR123A battery (3V) *1
CE, FCC, ETL, NCC, SRRC
Storage Temperature(-20~80°C)
Operating Temperature (10~35°C)
Black, White







Opro9 Smart Station

Center of the smart home ecosystem and make all thedevices work seamlessly.

Model Number LS082WH
Operating Temperature -5~45°C
Operating Humidity 5~90%
Power Supply DC 5V
Power Consumption <2.5W

Interfaces Power supply / RJ45 / Reset hole

Indicator Yes Connected Devices 500

Network LAN (10/100/1000 BASE-T via RJ45 port)

Color Ivory white

Dimensions 110.8*110.8*28mm

Weight 120g Casing ABS









Opro9 CUBE Motion Sensor

A tiny Motion sensor combined PIR technology and light detection.

Model Number
Operating Temperature
Operating Humidity
Power Supply
Static Consumption
Battery Life
Sensitive Element
Detection
Indicator
Color
Dimensions
Weight

Casing

LS062WH / LS150WH (Japan)

-5~45°C 5~90%

1 Battery CR2450, 3V

<1mW Up to 1 year

Passive infrared sensor, light sensor

5m/120° LED

lvory white 38.4*38.4*22.4mm

20 g ABS+PC







Opro9 CUBE Door / Window Sensor

A simple-to-install door/window sensor combined magnetic sensor and vibrating sensor.

Model Number
Operating Temperature
Operating Humidity
Power Supply
Static Consumption
Battery Life
Sensitive Element
Detection

Button Indicator Color Dimensions Weight Casing LS058WH / LS149WH (Japan)

-5~45°C 5~90%

1 Battery CR2450, 3V

<1 mW

Up to 1 year

Magnetic sensor, vibration sensor Slide and shake detection of the

door and window

Customizable button, pairing button

LED

Ivory white

38.4*38.4*14.6mm

20g ABS+PC







Opro9 CUBE Environmental Sensor

One device to simultaneously monitor the temperature, humidity and illumination and indicate these data with a LCD display.

Model Number
Operating Temperature
Operating Humidity
Power Supply
Static Consumption
Battery Life
Sensitive Element

Detection Button Indicator Display Color Dimensions Weight Casing LS063WH / LS091WH (Japan)

-5~45°C

5~90%

1 Battery CR2450, 3V

<1mW

Up to 1 year

Temperature sensor,

humidity sensor, light sensor Temperature, humidity, light

Pairing button

LED

LCD

Ivory white

38.4*38.4*16.2mm

24g

ABS+PC









Opro9 Water Leak Sensor

Ensure safety and the comfort of use when there is water leak.

Model Number
Operating Temperature
Operating Humidity
Detecting Types
Sensors
Power Supply
Power Consumption

Battery Life Interface Button Indicator Color Dimensions Weight Casing LS064WH
-5~45°C
5~90%
Water leak
Leak sensor
1 Battery CR2450, 3v
Static consumption<30µw
Alarm consumption<100mw
Up to 1 year
Water sensing probe
Pairing button
LED



Ivory white

31g

ABS+PC

50*72*20mm







Opro9 Moonstone Switch 120

Touchable switch leads you into a simple smart life.

Wiring
Control Unit
Operating Temperature
Operating Humidity
Power Supply
Static Consumption
Maximum Overload

Indicator Color

Dimension Casing Live+neutral

16A magnetic latching relay

5~45°C 5~90%

AC 100-240V 50/60Hz

<1.5W

Resistive load: 500W per channel

Inductive/Capacitive load: 200W per channel

16Million colors

White glass+White frame/ Black glass+White frame

120*72*35mm

Bottom cover: PC, top cover: ABS+PC,

front panel: glass















Opro9 Starry Switch

A tiny Motion sensor combined PIR technology and light detection.

Control Unit
Operating Temperature
Operating Humidity
Power Supply
Static Consumption
Maximum Overload

Battery Type Battery Lfie Color Dimension Casing 16A magnetic latching relay
-5~45°C
5~90%
DC 5V-30V Or AC 90-250V
<1mW
Resistive load: 500W per channel
Inductive/Capacitive load: 200W per channel
DC load: 30V/5A

ER18505M(substitute: CR17505 or ER17505) 5 years White / Black / Golden 86*86*39mm ABS+PC













Smart Curtain Motor

Turn your traditional curtains into smart ones.

Model Number Moving Speed Rated Torque Operating Temper

Operating Temperature
Operating Humidity
Ingress Protection
Power Supply
Power Consumption
Power Cable Length
Interface

Indicator

Maximal Track Length Maximal Load

Color
Dimensions

Weight Casing LS133WH 14cm/s 1.2Nm -5~45°C

5~90% IP40

AC 100V-240V 50/60Hz

13W 125cm Serial port

Weak urrent switch interface

LED 8m 50Kg White

365*60*50mm 1.3KG

Aircraft aluminum







Light Strip

A perfect 16 million colors lighting strip with adjustable brightness and preset modes to provide different atmospheres.

Model Number
Lighting Color
Luminous Flux
Operating Temperature
Operating Humidity
Power Supply
Power Consumption
Color
Dimensions
Weight

LS065

16 million colors + white

360lm -5~45°C 5~90%

DC 24V <12W/m

_ __

2000*12*3.5mm

Light strip weight: 114g/2meters











Opro9 BLEND Light Bulb - E27

A perfect 16 million colors lighting bulb with adjustable brightness and preset modes for lighting up your home.

Model Number Lighting Color Lamp Model Luminous Flux Operating Temperature Operating Humidity Power Supply Power Consumption

Color Dimensions Weight Casing

LS024

16 million colors + white

E27 220lm -5~45°C

5~90%

AC 100-240V 50/60Hz Static consumption<0.5W

Nominal consumption : 6W (RGB

3W, white 3W) Silver

Ø50*110mm

78g

Aluminum alloy











Opro9 Smart Plug - EU&FR

EU&FR standard plug, changing traditional electronic appliances to be smart ones.

Model Number
Operating Temperature
Operating Humidity
Operating Voltage
Static Consumption
Maximum Overload
Button
Indicatior
Electricity Metering
Manual Control
Installation
Socket Standard
Color
Dimension
Weight

Casing

LS159
-5~45°C
5~90%
AC 100-240V 50/60Hz
≤0.5W
16A
Pairing/operating button
RGB LED
Yes
Yes
Plug and play
EU & FR socket
Ivory white
61*61*84mm
95g
Flameresistant PC















Opro9

CviCloud

CviLux Group

